

Claims

The claims defining the invention are as follows:

1. A retrieval aid intended for use with a flexible line having an object located at the end of the line, the retrieval aid comprising a shaft having a line engagement member mounted at one end, said engagement member being readily engagable with the line whereby when engaged with the line the engagement member surrounds the line and is capable of movement along the line wherein the engagement member is formed as a coil comprising more than one turn but less than two turns and wherein the plane of the engagement member is inclined to the central axis of the shaft and extends outwardly from the end of the shaft.
2. A retrieval aid intended for use with a flexible line having an object located at the end of the line, the retrieval aid comprising a shaft having a line engagement member mounted at one end, said engagement member being readily engagable with the line whereby when engaged with the line the engagement member surrounds the line and is capable of movement along the line wherein the engagement member is formed as a coil comprising more than one turn but less than two turns which is arcuate through out its extent with the turns overlying each other with one end being fixed to the shaft and the other end being the free end, the portion of the coil; proximate the free end extending outwardly from the perimeter of the underlying turn and wherein the plane of the engagement member is inclined to the central axis of the shaft and extends outwardly from the end of the shaft.
3. A retrieval aid as claimed at claim 1 or 2 wherein the engagement member is supported from the one end of the shaft to extend to one side of the shaft.
4. A retrieval aid as claimed at claim 1 or 2 or 3 wherein the adjacent portions of the turns of the coil are spaced from each other.

- 14 -

5. A retrieval aid as claimed at claim 1 or 2 or 3 or 4 wherein the coil comprises a approximately $1\frac{1}{4}$ turns.
6. A retrieval aid as claimed at claim at any one of the preceding claims wherein the base of the coil to which the shaft is attached is axially outermost relative to the shaft and the remainder of the coil.
7. A retrieval aid as claimed at any one of claims 1 to 5 wherein the base of the coil to which the shaft is attached is axially innermost relative to the shaft and the remainder of the coil.
8. A retrieval aid as claimed at any one of the preceding claims wherein the shaft is extendable.
9. A retrieval aid as claimed at claim 8 wherein the shaft comprises a plurality of lengths which can be interconnected into an end to end relationship.
- 10.A retrieval aid as claimed at claim 9 wherein each end of each length is provided with a threaded fitting which can be threadably engaged with a complementary fitting of another length to enable said ends to end interconnection.
- 11.A retrieval aid as claimed at any one of the preceding claims wherein the shaft is resiliently flexible.
- 12.A retrieval aid as claimed at claim 11 wherein the shaft is formed of a fibre reinforced plastics material.
- 13.A retrieval aid as claimed at any one of the preceding claims wherein the shaft supports a retention member which is slidable along the shaft and a cord is fixed at one end to the retention member, the shaft being formed to prevent disengagement of the retention member from either end of the shaft.

- 15 -

14. A retrieval aid as claimed at any one of the preceding claims wherein said coil has an internal diameter less than the width of object supported by the line.
- 5 15. A retrieval aid as claimed at any one of claims 1 to 13 wherein said coil has an internal diameter greater than the width of object supported by the line.
16. A retrieval aid as claimed at any one of the preceding claims wherein the line comprises a fishing line and the object comprises a fish hook and/or lure.
- 10 17. A retrieval aid as claimed at any one of the preceding claims wherein the device can be used to retrieve a fish hook from the body of a fish.
18. A retrieval aid as claimed at any one of the preceding claims wherein the shaft supports at least one stand-off coil intermediate the length of the shaft, said stand-off coil comprises more than one turn wherein the central axis of the coil is substantially parallel to the shaft.
- 15 19. A retrieval aid as claimed at claim 18 wherein the stand-off coil is removably supported from the shaft.
20. A retrieval aid as claimed at claim 18 as dependant from claim 9 or 10 wherein the stand-off coil is adapted to be clampingly received between the ends of a pair of interconnected lengths.
- 20 21. A retrieval aid as claimed at any one of the preceding claims wherein the plane of the coil is at an obtuse angle to the shaft of between 100 and 150 degrees.
- 25 22. A retrieval aid as claimed at any one of the preceding claims wherein the coil has a length greater than one revolution and the free end of the coil extends outwardly from the outer perimeter of the coil.

- 16 -

23. A retrieval aid as claimed at claim 22 wherein the central axis of the free end subtends an angle of less than 90° to the central axis of the shaft.

24. A retrieval aid substantially as herein described with reference to the accompanying drawings.